

## Specifications

|   |   |
|---|---|
| <b>Model / MFS15</b>                        |   |
| <b>Engine (No. of Cylinder)</b>             | 2   |
| <b>Output</b>                               | 15 hp (11 kw)   |
| <b>Displacement</b>                         | 351 cc (21.41 cu.in.)   |
| <b>Bore x Stroke</b>                        | 61 x 60 mm (2.4 x 2.36 in)  |
| <b>Starting</b>                             | Electric or Manual  |
| <b>Control Type</b>                         | Remote Control or Tiller Handle   |
| <b>Gear Shift</b>                           | Forward - Neutral - Reverse   |
| <b>Gear Ratio</b>                           | 2.15:1  |
| <b>Propeller Selection Range</b>            | 6" - 10"  |
| <b>Transom Height</b>                       | 15", 20"  |
| <b>Fuel</b>                                 | Unleaded Gasoline (87 Octane)   |
| <b>Oil Type</b>                             | NMMA Certified FC-W <sup>®</sup> 4-stroke oil**<br>SAE 10W-30/40 (SF, SG, SH, SJ) |
| <b>Oil Capacity</b>                         | 1 qt. (1000 mL)   |
| <b>Fuel Tank</b>                            | 3.1 US Gal. (12 Lit) Separate Fuel Tank   |
| <b>Weight*</b>                              | 114.4 lbs. (52 kg)  |
| <b>Alternator Output</b>                    | Optional: 12V, 145W, 12A<br>(Standard on Electric Start Models)                   |
| <b>Max. RPM Range</b>                       | 5,000 - 6,000   |
| <b>Digital CD Ignition System</b>           | S   |
| <b>Start In Gear Protection</b>             | S   |
| <b>Thermostat Controlled Cooling System</b> | S   |
| <b>Through-The-Prop Exhaust</b>             | S   |
| <b>Shallow Water Drive</b>                  | S   |
| <b>Oil Pressure Warning</b>                 | S   |
| <b>Power Tilt</b>                           | O   |

**LEGEND:**

S.....Standard Features

O.....Optional on Certain Models

### Tohatsu 4-stroke benefits:

- Light and compact!
- Designed with proven technology
- Advanced cross-flow induction for smooth operation
- Canister style oil filter for easy replacement
- Larger capacity oil reservoir for optimum lubrication
- Tuned intake system for crisp takeoffs
- Ultra low emission, EPA and CARB approved
- 3 Year limited warranty

### High performance and easy operation:

- Digital CD ignition for easier engine starting, quicker throttle response and smoother trolling
- Recoil starter with larger reel making manual starting fast and easy
- Large alternator and rectifier for superior battery charging\*
- Front mounted shift lever for easier operation
- Remote control models available
- Shallow water drive
- 6 trim positions\*
- Adjustable steering friction for reducing steering effort\*


### Fundamentals for user convenience and reliability:

- Through-the-prop exhaust for a quieter ride
- Thermostatically controlled cooling system for consistent engine temperature
- Stainless steel water pump housing liner for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection against corrosion
- Zinc coating on internal water passages for superior corrosion resistance
- 3.1 gallon (12 liter) Fuel Tank including fuel fittings and fuel line
- Aluminum propeller

### Warning and protection:

- Low oil pressure warning (visual and audible\*\*)
- Start-in-gear protection for safer engine starting
- Safety lanyard (an essential protection feature standard on all Tohatsu outboards)
- Over-rev. limiter



 [More Photos](#)

When it's time for a some "father-daughter time", the Tohatsu 15hp 4-stroke is the perfect combination of power & reliability. Your Tohatsu is always ready...what are you waiting for?

Available in "short" and "long" shaft models, the Tohatsu 15hp 4-stroke is ideal for small fishing boats and inflatables. As with all Tohatsu models, these engines are coated with a specially formulated acrylic resin to help protect the engine from UV and saltwater damage.

 [Brochure Download](#)

 [Manual Download](#)



Exceeds the Federal EPA emission requirements for the year 2006.

\*Certain models

\*\* Remote control models



California C.A.R.B.  
three star rating  
for ultra-low emissions.

