

## Specifications

<b>Model / MFS25</b>	
<b>Engine (No. of Cylinder)</b>	3
<b>Output</b>	25 hp (18.4 kw)
<b>Displacement</b>	526 cc (32.09 cu.in.)
<b>Bore x Stroke</b>	61 x 60 mm (2.4 x 2.36 in)
<b>Starting</b>	Electric or Manual
<b>Control Type</b>	Remote Control or Tiller Handle
<b>Gear Shift</b>	Forward - Neutral - Reverse
<b>Gear Ratio</b>	1.92:1
<b>Propeller Selection Range</b>	8" - 14"
<b>Transom Height</b>	15", 20"
<b>Fuel</b>	Unleaded Gasoline (87 Octane)
<b>Oil Type</b>	NMMA Certified FC-W <sup>®</sup> 4-stroke oil** SAE 10W-30/40 (SF, SG, SH, SJ)
<b>Oil Capacity</b>	2 qt. (1800 mL)
<b>Fuel Tank</b>	6.6 US Gal. (25 Lit) Separate Fuel Tank
<b>Weight*</b>	157 lbs. (71.5 kg)
<b>Alternator Output</b>	12V, 180W, 15A
<b>Max. RPM Range</b>	5,000 - 6,000
<b>Electric Fuel Injection</b>	S
<b>Digital CD Ignition System</b>	S
<b>Start In Gear Protection</b>	S
<b>Thermostat Controlled Cooling System</b>	S
<b>Through-The-Prop Exhaust</b>	S
<b>Shallow Water Drive</b>	O
<b>Oil Pressure Warning</b>	S
<b>Power Trim and Tilt</b>	O
<b>Gas Assist Tilt</b>	O

### LEGEND:

S.....Standard Features

O.....Optional on Certain Models

### Tohatsu 4-stroke benefits:

- Designed with proven technology
- Advanced cross-flow induction for smooth operation
- Canister style oil filter for easy replacement
- Larger capacity oil reservoir for optimum lubrication
- Tuned intake system for crisp takeoffs
- Ultra low emission, EPA and CARB approved
- 3 Year limited warranty

### High performance and easy operation:

- Electronic fuel injection
- The boating industry's first battery-free, manual start EFI 4-stroke
- Digital CD ignition system for quicker starts
- Large alternator and rectifier for superior battery charging
- Adjustable steering friction and trim tab for reducing steering effort
- Front mounted shift lever for easier operation
- Shallow water drive, 6 tilt positions\*
- Gas assisted shocks\*
- Power trim & tilt\*
- Remote control\*\*

### Fundamentals for user convenience and reliability:

- Through-the-prop exhaust for a quieter ride
- Thermostatically controlled cooling system for consistent engine temperature
- Stainless steel water pump housing liner for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection against corrosion
- Zinc coating on internal water passages for superior corrosion resistance
- 6.6 gallon (25 liter) Fuel Tank including fuel fittings and fuel line
- Aluminum propeller

### Warning and protection:

- Overheat warning (audible)
- Low oil pressure warning (audible)
- Start-in-gear protection for safer engine starting
- Safety lanyard (an essential protection feature standard on all Tohatsu outboards)
- Over-rev. limiter

\*Certain models  
\*\* Remote control models