

Specifications

Model / MFS30	
Engine (No. of Cylinder)	3
Output	30 hp (22.1 kw)
Displacement	526 cc (32.09 cu.in.)
Bore x Stroke	61 x 60 mm (2.4 x 2.36 in)
Starting	Electric or Manual
Control Type	Remote Control or Tiller Handle
Gear Shift	Forward - Neutral - Reverse
Gear Ratio	1.92:1
Propeller Selection Range	8" - 14"
Transom Height	15", 20"
Fuel	Unleaded Gasoline (87 Octane)
Oil Type	NMMA Certified FC-W® 4-stroke oil** SAE 10W-30/40 (SF, SG, SH, SJ)
Oil Capacity	2 qt. (1800 mL)
Fuel Tank	6.6 US Gal. (25 Lit) Separate Fuel Tank
Weight*	157 lbs. (71.5 kg)
Alternator Output	12V, 180W, 15A
Max. RPM Range	5,250 - 6,250
Electric Fuel Injection	S
Digital CD Ignition System	S
Start In Gear Protection	S
Thermostat Controlled Cooling System	S
Through-The-Prop Exhaust	S
Shallow Water Drive	O
Oil Pressure Warning	S
Power Trim and Tilt	O

LEGEND:

S.....Standard Features

O.....Optional on Certain Models

Tohatsu 4-stroke benefits:

- Designed with proven technology
- Advanced cross-flow induction for smooth operation
- Canister style oil filter for easy replacement
- Larger capacity oil reservoir for optimum lubrication
- Tuned intake system for crisp takeoffs
- Ultra low emission, EPA and CARB approved
- 3 Year limited warranty

High performance and easy operation:

- Electronic fuel injection
- The boating industry's first battery-free, manual start EFI 4-stroke
- Digital CD ignition system for quicker starts
- Large alternator and rectifier for superior battery charging
- Adjustable steering friction and trim tab for reducing steering effort
- Front mounted shift lever for easier operation
- Shallow water drive, 6 tilt positions*
- Gas assisted shocks*
- Power trim & tilt*
- Remote control**

Fundamentals for user convenience and reliability:

- Through-the-prop exhaust for a quieter ride
- Thermostatically controlled cooling system for consistent engine temperature
- Stainless steel water pump housing liner for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection against corrosion
- Zinc coating on internal water passages for superior corrosion resistance
- 6.6 gallon (25 liter) Fuel Tank including fuel fittings and fuel line
- Aluminum propeller

Warning and protection:

- Overheat warning (audible)
- Low oil pressure warning (audible)
- Start-in-gear protection for safer engine starting
- Safety lanyard (an essential protection feature standard on all Tohatsu outboards)
- Over-rev. limiter

*Certain models
** Remote control models