

Specifications

Model / MFS6	
Engine (No. of Cylinder)	1
Output	6 hp (4.4 kw)
Displacement	123 cc (7.5 cu.in.)
Bore x Stroke	59 x 45 mm (2.32 x 1.77 in)
Starting	Manual
Control Type	Tiller Handle
Gear Shift	Forward - Neutral - Reverse
Gear Ratio	2.15:1
Propeller Selection Range	6" - 9"
Transom Height	15", 20", 25"
Fuel	Unleaded Gasoline (87 Octane)
Oil Type	NMMA Certified FC-W [®] 4-stroke oil** SAE 10W-30/40 (SF, SG, SH, SJ)
Oil Capacity	15 fl. oz. (450 mL)
Fuel Tank	3.1 US Gal. (12 Lit) Separate Fuel Tank
Weight*	55 lbs. (25 kg)
Alternator Output	Optional: 12V, 60W, 5A (Standard on 25" shaft model)
Max. RPM Range	5,000 - 6,000
Digital CD Ignition System	S
Start In Gear Protection	S
Thermostat Controlled Cooling System	S
Through-The-Prop Exhaust	S
Shallow Water Drive	S
Oil Pressure Warning	S

LEGEND:

S.....Standard Features

O.....Optional on Certain Models

Tohatsu 4-stroke benefits:

- Light and compact!
- Designed with proven technology
- Greatly reduced vibration for smooth and stable running at all speeds
- Greatly reduced induction noise for a quieter ride
- Ultra Low emission, EPA and CARB approved
- 3 Year limited warranty

Easy operation and handling:

- Digital CD ignition for easier engine starting, quicker throttle response and smoother trolling
- Recoil starter with larger reel making manual starting fast and easy
- Shallow water drive
- 6 trim positions
- Adjustable steering friction for reducing steering effort

Fundamentals for user convenience and reliability:

- Through-the-prop exhaust for a quieter ride
- Thermostatically controlled cooling system for consistent engine temperature
- Stainless steel water pump housing liner for outstanding durability
- High grade marine aluminum alloy that provides the ultimate protection against corrosion
- Zinc coating on internal water passages for superior corrosion resistance
- Plastic fuel tank with fuel gauge on the cap
- Aluminum propeller

Protection:

- Low oil pressure indicator
- Safety lanyard (an essential protection feature standard on all Tohatsu outboards)
- Start-in-gear protection for safer engine starting
- Over-rev. limiter